



Hangcha Europe GmbH

Mariechen-Graulich-Straße 12a,
65439 Flörsheim am Main,
Germany

Administration
Tel: 0049-61453769188
E-mail: admin@hangchaeurope.com

Sales Management
Thomas Dittrich
Mob: 0049-16096548808
E-mail: thomas.dittrich@hangchaeurope.com

Technical Support
Thomas Pannke
Mob: 0049-01759284213
E-mail: thomas.pannke@hangchaeurope.com

www.hangchaeurope.com



Folgen Sie uns auf
Instagram



Folgen Sie uns auf
Facebook



Folgen Sie uns auf
YouTube



"Hangcha Forklift"
App herunterladen



ISO14001:2015



ISO9001:2015



HANGCHA trucks conform
to the European Safety
Requirements.

HANGCHA Group Co., LTD behält sich das Recht vor, Änderungen bezgl. Farbe, Spezifikationen, Ausstattung und sonstige Details, dieser Broschüre ohne Vorankündigung vorzunehmen. Fahrzeugfarben können von den Farben in dieser Broschüre abweichen.

2025 VERSION 2/COPYRIGHT 2025/05



X Series Internal Combustion Tractor

with capacities of 3,500 to 8,000kg

The World of Hangcha
SINCE 1956



X Series Internal Combustion Tractor

Representing the design concept of safety, reliability, comfort and environmental protection, Hangcha's X series 3.5-8.0 ton internal combustion tractor has the features of high power, large traction force, high operating efficiency, etc. and is suitable for medium and short distances and point-to-point logistics transportation.



Exterior


- / The body has a stylish profile formed by a combination of large arcs and streamlined curved surfaces. The easy pass-through chassis and the cab are arranged appropriately, bringing visual tension and sense of power and following the latest international trend of exterior design.
- / The vehicle is compact in appearance and the exposed parts are environmentally friendly large stamped metal parts, which are robust and reliable. The interior is composed of large injection molded parts, which are integrally molded, fully cover the inside and are luxurious and generous.

Safety and reliability

- / The front part, beam, etc. which are molded with 20mm thick steel plates and the welded body, all have high strength and are suitable for pushing operations.
- / Two sets of independent air-push-liquid all-wheel braking systems, with double pipelines arranged in an X shape and front and rear partial pressure, enable safe, stable and reliable braking and are suitable for remote control of trailer braking. With the air cylinder design, they can even brake reliably when not powered.
- / The foolproof self-limited gear shifter makes gear shifting easy and reliable.
- / The traction device with a safety buckle and self-locking function provides double protection and prevents the traction pin from jumping or being mis-operated.
- / With the electrical main switch, emergency shut-off and stalling can be performed safely and reliably.

Comfort

- / With the human-machine interaction system that consists of compact and reliable novel digital multifunctional instruments with clear liquid crystal displays, a combination rocker switch and a standard speedometer, the operations of the vehicle can be shown clearly.
- / Special forklift technologies such as a horizontal cylinder steering axle, a full hydraulic steering gear, etc. are used and the steering force is less than 10N.
- / The advanced chassis elastic suspension technology and the long wheelbase and large flexibility design enable a great ride comfort.
- / The wide-view cab with an integral frame is flexibly connected to the body, and has good sealing, sound insulation, vibration isolation and heat insulation, etc. It is equipped with a cooling and heating air conditioner to improve the driver's comfort and operating ease.



Environmental protection

- / Well matching the high-efficiency gearbox, the low-speed and high-torque engine provides strong power and enables high efficiency and good economy of the vehicle.
- / The emission complies with national standards, and a higher level of environmental protection configuration is optional (in compliance with the national test standard IV).
- / Asbestos-free materials, which can be recycled and reused, are used for the vehicle.

Maintainability

- / With the design of a wide-opened hood, when the hood is opened, the engine, fuel tank, water tank, oil pump, steering gear, etc. are all exposed to facilitate repair and maintenance.
- / The electrical controllers, battery, etc. are arranged concentratedly and the fuses are installed separately to facilitate maintenance.



Standard Specification

- / Headlights (high-beam and low-beam)
- / Turn signal lights
- / Combination LED tail lights
- / Oil gauge
- / Water thermometer
- / Engine hour counter
- / Engine oil pressure alarm
- / Gearbox oil temperature alarm
- / Gearbox oil pressure meter
- / Fully-suspended seat
- / Electric horn
- / Reverse buzzer
- / Main power switch
- / Speedometer
- / Cup holder
- / Fire extinguisher
- / Front wiper
- / Reflective mirror
- / Rearview mirror
- / Ceiling light
- / Large integral rubber pedal pads
- / Boarding handle
- / Fully hydraulic steering
- / Steering wheel adjusting device
- / Air-push-liquid braking system
- / Heater
- / Front glass defroster
- / Neutral gear safety switch

Options

- / Police light
- / Rear work light
- / Speed limit alarm
- / Traction pin height scheme
- / Awning
- / Front wiper
- / Air conditioner
- / Fuel tank cap locked
- / Front hook
- / Solid tire
- / Remote trailer braking and electrical output
- / User specified colors
- / Tool box



X Series 3.5-8.0t Internal Combustion Tractor Specification

Distinguishing mark	1.1	Manufacturer		HANGCHA GROUP CO.,LTD.						
	1.2	Manufacturer's type designation		QCD35-XG87	QCD40-XG87	QCD45-XG87	QCD50-XG87	QCD60-XG90	QCD70-XG90	QCD80-XG90
	1.3	Drive: electric (battery or mains), diesel, petrol, fuel gas		Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel
	1.7	Rated drawbar pull	N	35000	40000	45000	50000	60000	70000	80000
		Towing Weight(one pallet)	kg	47000	53000	60000	66000	80000	90000	100000
		Towing Weight(Two pallet)	kg	70000	80000	90000	100000	120000	135000	150000
Weight	1.9	Wheelbase	y (mm)	2170	2170	2170	2170	2170	2170	2170
	2.1	Service Weight	kg	5800	6300	6800	7300	8600	9600	10600
	2.3	Axle loading, unladen front/rear	kg	1750/4050	1750/4550	1750/5050	1750/5550	1750/6850	1750/7850	1750/8850
Tyres, chassis	3.2	Tyre size, front		2-7.00-12-12PR				2-7.50-16-14PR		
	3.3	Tyre size, rear		4-7.50-16-14PR		4-8.25-15-14PR		4-9.00-20-14PR 4-8.25-15-14PR		
	3.6	Tread, front	b10 (mm)	1740				1715		
	3.7	Tread, rear	b11 (mm)	1420				1600		
Dimensions	4.7	Height of overhead guard (cabin)	h6 (mm)	2422				2522		
	4.12	Coupling height	h10 (mm)	470				470		
	4.19	Overall length	l1 (mm)	3825				3865		
	4.21	Overall width	b1 (mm)	1930				1930		
	4.32	Ground clearance, centre of wheelbase	m2 (mm)	200				200		
	4.35	Turning radius	Wa (mm)	3850				4450		
Performance data	5.1	Travel speed, laden/unladen	km/h	-/22				-/24		
	5.7	Gradeability, laden/unladen	%	-/30				-/30		
	5.10	Service brake		Steam Push Fluid				Steam Push Fluid		
		Parking brake		Mechanical				Mechanical		
Combustion-engine	7.1	Engine manufacturer/type		YUCHAI/YCA05115-T480				YUCHAI/YCA07160-T400		
		Emission STD.		CN Stage IV				CN Stage IV		
	7.2	Engine power according to DIN ISO 1585	kw	85				118		
	7.3	Rated speed	min	2200				2200		
	7.4	Number of cylinders/displacement	(-)/(cm³)	-/4837				-/6870		
	7.10	Battery voltage/nominal capacity	V/Ah	24/90				24/90		
		Rated Torque	N·m/(r/min)	480/1600-1800				670/1400-1700		
		Bore×Stroke	mm	108×132				108×125		
		Transmission Manufacture		CHINA				CHINA		
		Transmission Type		Powershift				Powershift		
	Gear Fwd/Rvs		2/1				2/1			
	10.4	Fuel tank capacity	liter	165				165		

